



KINO FLO
Lighting Systems

Imara®

Universal VAC



Imara[®] DMX



The Imara[®] S100 and S60 studio softlight fixtures have the characteristics of the Image series, but with a more concentrated spread of light along both horizontal and vertical axes. The Imara S100 delivers 4K worth of softlight using only 4.3A (120VAC). The Imara S60 only requires 2.5A (120VAC). The all-in-one Imara DMX fixtures feature new universal input voltage from 100-240VAC along with onboard and remote lamp dimming and switching, making them ideal for film production, TV broadcast and digital photography. Both models use Kino Flo's True Match[®] high color rendering 55W compact lamps (CRI 95) available in tungsten and daylight. Features include:

- DMX and manual lamp switching
- DMX and manual lamp dimming
- DMX Auto Terminate
- Universal input 100VAC-240VAC
- Reflector, Louver and Gel Frame
- Yoke Mount, Pole-Op
- True Match[®] daylight, tungsten balanced lamps

▼ Photometrics

Imara S100	FC	1880	661	323	187	123	87	66	51	41	34
	Feet	2	4	6	8	10	12	14	16	18	20

Imara S60	FC	1470	447	207	119	77	54	41	32	25	21
	Feet	2	4	6	8	10	12	14	16	18	20

Imara S100	LUX	25500	9900	4960	2930	1930	1370	1030	796	642	524
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

Imara S60	LUX	20900	6970	3240	1890	1230	861	639	494	396	323
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

▼ Fixture Specifications

Fixture	Input Voltage	Output Frequency	Dimming Range	Lamp Switching	Amps	Lamps	Dimensions	Weight w/Lamps
Imara S100 DMX	100-240VAC 50/60Hz	80kHz	100-5%	2/4/6/8/10	4.3A	10 x 55W CFL	41 x 27 x 7" (104 x 68.5 x 18cm)	31 lb (14kg)
Imara S100 DMX	240-100VAC 50/60Hz	80kHz	100-5%	2/4/6/8/10	2.1A	10 x 55W CFL	41 x 27 x 7" (104 x 68.5 x 18cm)	31 lb (14kg)
Imara S60 DMX	100-240VAC 50/60Hz	80kHz	100-5%	2/4/6	2.5A	6 x 55W CFL	28 x 27 x 7" (71 x 68.5 x 18cm)	21 lb (9.5kg)
Imara S60 DMX	240-100VAC 50/60Hz	80kHz	100-5%	2/4/6	1.3A	6 x 55W CFL	28 x 27 x 7" (71 x 68.5 x 18cm)	21 lb (9.5kg)

▼ Details



▼ Imara S100 DMX




IMR-S100-120U
Imara S100 DMX Yoke,
Univ 120U



IMR-S100P-120U
Imara S100 DMX Pole-Op,
Univ 120U



IMR-S100P-230U
Imara S100 DMX Pole-Op,
Univ 230U



GFR-IM10
Imara S100 Gel Frame
(Included)

LVR-IM1090
Imara S100 Louver, 90°
(Included)


▼ Imara S60 DMX




IMR-S60-120U
Imara S60 DMX Yoke,
Univ 120U



IMR-S60P-120U
Imara S60 DMX Pole-Op,
Univ 120U




IMR-S60P-230U
Imara S60 DMX Pole-Op,
Univ 230U




GFR-IM6
Imara S60 Gel Frame
(Included)

LVR-IM690
Imara S60 Louver, 90°
(Included)

▼ Imara Accessories/ Lamps



BRD-IM10
Imara S100 Barndoors




BRD-IM6
Imara S60 Barndoors



LVR-IM1060
Imara S100 Louver, 60°



LVR-IM660
Imara S60 Louver, 60°



MTP-180
Junior Pin Assembly for Yoke
(28mm)



KAS-IM10-1
Imara S100 Ship Case



KAS-IM6-1
Imara S60 Ship Case



KAS-CL6
6-Lamp Carry Case
(55W Compact)



55C-K32
55W Kino KF32 Compact



55C-K55
55W Kino KF55 Compact



KINO FLO[®]
Lighting Systems

2840 North Hollywood Way, Burbank CA 91505 +1 818 767 6528 voice

www.kinoflo.com

No. 3110093