



KINO FLO
Lighting Systems

FreeStyle Mini **LED**



FreeStyle Mini LED DMX



▼ Details



▼ Photometrics

FreeStyle Mini	FC	195	54	24	14	9	6	5	4	3	2
	Feet	2	4	6	8	10	12	14	16	18	20
	LUX	3060	828	380	219	142	99	73	57	45	37
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

▼ Fixture Specifications

Fixture	Kelvin Range	Dimming Range	Dimensions	Weight
FreeStyle Mini	2500-9900	100%-1%	15 x 3 x 7.5" (38 x 8 x 19cm)	3.5 lb (2kg)

▼ LED Controller Specifications

Controller	Input VAC	Amps VAC	Input VDC	Amps 24VDC	Kelvin Range	Dimming Range	Dimensions	Weight
LED-120X	100-240VAC, 50/60Hz, 100W	0.83A 0.43A	18-36VDC, 100W	4.2A	2500-9900	100%-1%	9.5 x 7 x 2.5" (24 x 18 x 6.5cm)	4 lb (2kg)

▼ FreeStyle Mini LED DMX Kit

KIT-F10BU

FreeStyle Mini LED DMX Kit, Univ

Contents

- 1 FreeStyle Mini LED Fixture
- 1 FreeStyle 120 LED DMX Controller
- 1 MTP-BG41S Mount w/
Baby Receiver Short (16mm)
- 1 Extension, 25ft
- 1 Soft Case

Dimensions
18.5 x 9.5 x 13.5"
(47 x 24 x 34cm)

Weight
15 lb
(7kg)

▼ FreeStyle Mini LED DMX System



CFX-F10
FreeStyle Mini LED
Fixture



LED-120X-120U
FreeStyle 120 LED
DMX Controller,
Univ 120U



MTP-BG41S
KinoGrip 41K
Mount w/ Baby
Receiver Short
(16mm)




X08-F125
FreeStyle/1
Extension, 25ft

▼ FreeStyle Mini Accessories/Case



PAN-F10
FreeStyle Mini
LED Panel



LVR-FS1090-P
FreeStyle Mini
Louver/HP, 90°



MTP-KG41
KinoGrip 41K
Mount w/ 3/8"
Pin (10mm)



BAG-FS10
FreeStyle Mini
Soft Case

FreeStyle Mini LED has five menu options. With white menu, the Kelvin range is from 2700K to 6500K with **Dimming**, **Kelvin** and **Green/Magenta** control channels. In the first color menu, Kelvin range is from 2500K to 9900K, with three additional channels, **Gel**, **Hue Angle** and **Saturation**. The Gel channel includes Kino Flo presets such as blue & green screen and over 100 well-known lighting gels. The second color menu provides individual **RGB** (red, green, blue) control. The **CIE xy** menu allows you to enter xy coordinates. The **FX** (Effects) menu has custom presets like Candle, Fire, TV, Police, Lightning, Paparazzi, Pulse and Scroll. The controller comes with standard DMX, wireless DMX (Lumen Radio®), universal voltage input 100-240VAC and 24VDC.

Features include:

- Kelvin presets & custom settings, 2500K-9900K
- Dimming without color shift
- Green/Magenta control
- Dial in any color through Hue Angle and Saturation control
- Kino Flo presets and Gels
- RGB control
- CIE xy
- FX (Effects) control
- Camera Profiles (LUTs)
- Color Space
- Manual & DMX Dimming, DMX wireless (Lumen Radio)
- Twist-on, locking Center Mount and corner mount options