

# <u>Ongenieux</u>°

Type EZ Series

with







# Cine-Style and **ENG Type Applications**

Type EZ lenses are designed for full manual operation, with sufficient rotation angles for creative and precise focus, zoom and iris control. The lens mechanics are made with high-quality, lightweight metal for precision and durability, including temperature compensation to help-avoid recalibration.

Type EZ Zooms provide incredibly fast T-stops, large format sensor coverage, and thanks to their industry-standard 0.8 gear teeth on all three rings, are compatible with lens motors and follow focus units for Cine Style acquisition. The 114mm front diameter is matte box compatible, and a Type EZ Hood is available. For ENG shooting, a broadcast servo unit (the MSU), was designed specifically for Type EZ Zooms, and is compatible with a wide variety of hand controllers for remote lens control.

## One Lens For All

The versatile, future-proof Angénieux EZ series works with multiple camera formats, thanks to its dedicated groups customized for both \$35 Full Frame sensors ; based on Technology™ IRO (Interchangeable Rear Optics). Lens mounts are fully interchangeable, with PL, Canon EF and Sony E mounts currently available.

# EZ : with

# Ongenieux<sup>1</sup>

## Fast Aperture and Up to Full Frame

Type EZ lenses are available in either S35 or as a S35 & FF/VV package; and are among the fastest in the industry at f/1.9-T2.0 aperture for S35 cameras. They cover an image circle up to 30mm diagonal for cameras recording in HDTV/UDTV modes and APS-C format DSLRs. The large format option converts them into f/2.8-T3.0 lenses, covering an image circle up to 46mm diagonal.

The lenses perfectly match Full-Frame sensors by RED, ARRI, SONY and other cameras with larger image circles. In S35 cameras, the large format rear group also functions as a 1.5x extender, turning the 30-90mm T2.0 lens into a 45-135mm T3.0 lens.

No Crop Factors The 22mm/T3.0 wide-angle end for large format cameras converts the lens into a 15mm/T2.0 for S35 cameras, maintaining a similar field of view with extra gain in T-stop.

# O∩Qe∩ieUX Type EZ-1 (Standard)

### **Specifications**

Imaging coverage Zoom ratio Focal length **Aperture** MOD Reference image size Horizontal angular FOV Vertical angular FOV FOV at MOD at focal min FOV at MOD at focal max Front diameter Lenath Weiaht

S35-3 perf FF/VistaVision Up to 30 Up to 46 30 - 90 mm 45 - 135 mm f/1.9 - T2.0 f/2.8 - T3.0 2ft - 0.6m 2ft - 0.6m 24 x 13.5 37.7 x 24.9 43.6° - 15.2° 45.6° - 15.9° 30.8° - 10.7° 25.1° - 8.8° 334 x 184 mm 351 x 228 mm 115 x 77 mm 110 x 63 mm 114 mm 114 mm 226 mm 226 mm 4.7lb - 2.15ka 4.5lb - 2.05ka



STANDARD S35 REAR GROUP



STANDARD LARGE FORMAT REAR GROUP



## **ACCESSORIES**

#### **ENG Broadcast Style Servo unit**

An optional hand-hold grip can be attached to the Type EZ-lens series. It comes in two versions, the MSU-1 with 3 motors (zoom/focus/iris) or the MSU-1A with 1 motor (zoom). The grip has a build-in wireless module that provides a remote wireless lens control. Wireless lens controller also

Please contact your sales representative for required connecting cables.



**EZ Hood** 



**EZ Transport case** 



#### Interchangeable lens mount

The EZ lens series are supplied with a universal lens mount thread, allowing the lenses to be configured to PL, Sony-E, or Canon EF mounts. All lenses are supplied with one PL lens mount ring, andadditionallensmountringscanbepurchased separately when needed.







# Ongenieux Type EZ-2 (Wide)

#### **Specifications**

|                         | •              |                |
|-------------------------|----------------|----------------|
| Imaging coverage        | Up to 30       | Up to 46       |
| Zoom ratio              | 2.7x           | 2.7x           |
| Focal length            | 15 - 40 mm     | 22 - 60 mm     |
| Aperture                | f/1.9 - T2.0   | f/2.8 - T3.0   |
| MOD                     | 2ft - 0.6m     | 2ft - 0.6m     |
| Reference image size    | 24 x 13.5      | 37.7 x 24.9    |
| Horizontal angular FOV  | 77.6° - 33.7°  | 80.2° - 35°    |
| Vertical angular FOV    | 44.5° - 19.6°  | 57.4° - 24°    |
| FOV at MOD at focal min | 628 x 342 mm   | 658 x 426 mm   |
| FOV at MOD at focal max | 235 x 134 mm   | 245 x 165 mm   |
| Front diameter          | 114 mm         | 114 mm         |
| Length                  | 210 mm         | 210 mm         |
| Weight                  | 4.7lb - 2.12kg | 4.6lb - 2.07kg |
|                         |                |                |

S35-3 perf







FF/VistaVision



For more information on the Angénieux Type EZ Series, please contact

#### EUROPE/AFRICAS/EURASIA/MIDDLE EAST

Thales LAS France Boulevard Ravel de Malval 42570 Saint-Héand - FRANCE Phone: +33 (0)4 77 90 78 00

Email: angenieux@fr.thalesgroup.com

#### **AMERICAS**

Band Pro Film & Digital Burbank 3403 West Pacific Avenue Burbank, CA 91505 - USA

Phone: +1 818 841 9655 / 1-888-<u>BAND-PRO</u>

Email: sales@bandpro.com

#### **ASIA PACIFIC**

JEBSEN Hong-Kong 30/F, Lee Gardens Two, 28 Yun Ping Road, Causeway Bay, Hong Kong

Phone: +825 2926 2350 Email: jcinecast@jebsen.com













